



FOR FIRE  
SPRINKLER  
SYSTEMS

**MATERIALS OF  
CONSTRUCTION**

END FITTINGS - CARBON STEEL - SCH 40  
HOSE & BRAID - STAINLESS STEEL - 300 SERIES  
ELBOWS - CARBON STEEL - SCH 40

NOTE: FIREVOOP INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	4" (100mm)	VLUGHP160400	±8"	72-3/8"	30-1/2"	300	38	
	5" (125mm)	VLUGHP160500	±8"	71-7/8"	29-1/2"	300	59	
	6" (150mm)	VLUGHP160600	±8"	85-1/4"	35-1/2"	300	88	

SUITABLE FOR USE IN DRY PIPE SYSTEMS  
FOR TEMPERATURES TO -40°F.

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
<b>METRAFLEX FIREVOOP™</b> GROOVED ENDS, ±8" MOVEMENT, HP H&B	
DRAWN BY: <b>JIMA</b>	DATE: <b>4/15/2021</b>
APPROVED:	DATE:
SCALE: N/A	DRAWING NUMBER: <b>VLUGHP16</b>