



FOR FIRE  
SPRINKLER  
SYSTEMS

#### MATERIALS OF CONSTRUCTION

END FITTINGS - CARBON STEEL - SCH 40

HOSE & BRAID - 316 STAINLESS STEEL

ELBOWS - CARBON STEEL - SCH 40

NOTE: FIREVOOP INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	4" (100mm)	VLUGHP80400	±4"	58-5/8"	23-5/8"	300	38	
	5" (125mm)	VLUGHP80500	±4"	59-1/2"	23-1/4"	300	59	
	6" (150mm)	VLUGHP80600	±4"	70"	28"	300	88	

SUITABLE FOR USE IN DRY PIPE SYSTEMS  
FOR TEMPERATURES TO -40°F.

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV.	DATE	
		2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM
<b>METRAFLEX FIREVOOP™</b> GROOVED ENDS, +/- 4" MOVEMENT, HP H&B		
DRAWN BY: <b>JIMA</b>		DATE: <b>4/15/2021</b>
APPROVED:		DATE:
SCALE: <b>N/A</b>	DRAWING NUMBER: <b>VLUGHP8</b>	