



**MODEL FSUG8
GROOVED FLEXIBLE CONNECTOR
±8" MOVEMENT**



| QTY | PART NUMBER | PIPE SIZE | A | BRAID | PRESSURE RATING (PSI)* | INTERMITTENT LATERAL OFFSET |
|-----|-------------|-----------|---------|--------|------------------------|-----------------------------|
| | FSUG80100 | 1" | 30-3/8" | SINGLE | 300 | 8" |
| | FSUG80125 | 1-1/4" | 32-1/2" | SINGLE | 300 | 8" |
| | FSUG80150 | 1-1/2" | 34-5/8" | SINGLE | 300 | 8" |
| | FSUG80200 | 2" | 37-7/8" | SINGLE | 300 | 8" |
| | FSUG80250 | 2-1/2" | 42-1/8" | SINGLE | 300 | 8" |
| | FSUG80300 | 3" | 43-1/4" | DOUBLE | 300 | 8" |
| | FSUG80400 | 4" | 47-3/4" | DOUBLE | 175 | 8" |
| | FSUG80500 | 5" | 50-1/4" | DOUBLE | 175 | 8" |
| | FSUG80600 | 6" | 52-3/4" | DOUBLE | 175 | 8" |
| | FSUG80800 | 8" | 57-3/4" | DOUBLE | 175 | 8" |
| | FSUG81000 | 10" | 62-5/8" | DOUBLE | 175 | 8" |
| | FSUG81200 | 12" | 67-5/8" | DOUBLE | 175 | 8" |

SUITABLE FOR USE IN DRY PIPE SYSTEMS
TEMPERATURES TO -40°F



NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

| | | |
|---|------------------------------|---|
| REV. 1 | SMALLER SIZES ADDED | DATE 9/9/2021 |
| | | 2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM |
| MODEL FSUG8 UL LISTED GROOVED FLEXIBLE CONNECTOR FOR FIRE PROTECTION, ±8" MOVEMENT | | |
| DRAWN BY: RDAHYA | | DATE: 12/11/2019 |
| APPROVED: _____ | | DATE: _____ |
| SCALE: N/A | DRAWING NUMBER: FSUG8 | |