



**MODEL FSUG2
GROOVED FLEXIBLE CONNECTOR±2"
MOVEMENT**



QTY	PART NUMBER	PIPE SIZE	A	BRAID	PRESSURE RATING (PSI)*	INTERMITTENT LATERAL OFFSET
	FSUG20100	1"	19-1/8"	SINGLE	300	2"
	FSUG20125	1-1/4"	19-5/8"	SINGLE	300	2"
	FSUG20150	1-1/2"	22-1/8"	SINGLE	300	2"
	FSUG20200	2"	22-3/8"	SINGLE	300	2"
	FSUG20250	2-1/2"	24-3/8"	SINGLE	300	2"
	FSUG20300	3"	25-1/4"	DOUBLE	300	2"
	FSUG20400	4"	26-3/4"	DOUBLE	175	2"
	FSUG20500	5"	28-1/4"	DOUBLE	175	2"
	FSUG20600	6"	30-3/4"	DOUBLE	175	2"
	FSUG20800	8"	37-3/4"	DOUBLE	175	2"
	FSUG21000	10"	36-5/8"	DOUBLE	175	2"
	FSUG21200	12"	38-5/8"	DOUBLE	175	2"

SUITABLE FOR USE IN DRY PIPE SYSTEMS
TEMPERATURES TO -40°F



NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	1	SMALLER SIZES ADDED	DATE	9/9/2021
		2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM		
		MODEL FSUG2 UL LISTED GROOVED FLEXIBLE CONNECTOR FOR FIRE PROTECTION, ±2" MOVEMENT		
DRAWN BY: RDAHYA		DATE: 12/11/2019		
APPROVED:		DATE:		
SCALE:	DRAWING NUMBER:			
N/A	FSUG2			